

Client	Quantity	
Project	Position	

## **ROC 700**

Model: R70/80CFE Cod: MP01034123001

## **Technical data**

Modularity:	Electric oven
Dimensions (mm):	800x730x870
Oven dimension (mm):	555x660x257
Total eletric power (kW):	16,4
Oven type:	Static oven
Oven power (kW):	6
Oven temperature range (°C):	50 - 300
Electric power (V):	380-415
Ampere (A):	25,5
Phases:	3N
Cable section (mmq):	5G4
Frequency (Hz):	50-60
Net volume (m3):	0,508
Packing dimensions (mm):	880x856x1109
Gross weight (kg):	111
Gross volume (m3):	0,835

## **Features**

Working top:	Made of AISI 304 stainless steel with a thickness of 20/10 mm
Knobs:	Made of aluminum with IPX5 water protection
Flue:	Removable gas exhaust flue grill made of cast iron


In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.





Electric range, 4 round plates, electric static oven

Electric hob with 4 round plates on electric oven. Side panels, bottom and back made in stainless steel. Pressed top made in AISI 304 thickness 20/10 with control edge for liquid collection iron designed for flush alignment. Rear flue made in enamelled cast-iron.N° 4 round electric plates diam.220 mm each with 2.6 kW, equipped with safety thermostat and automatic recovery. 6 levels temperature control for each plate. Lamp on control panel to indicate the activation of electric supply and plates operation. Electric static oven GN 2/1. Heating by electric upper and lower heating elements with indipendent regulation. Temperature regulation by thermostat, from 50 °C to 300 °C. Safety thermostat. Lamp on control panel to indicate oven heating activation. Cooking chamber made in stainless steel. Oven inner door made in stainless steel with labyrinth seal. Oven power 6 kW. Special design knobs to avoid water penetration in the control panel. Adjustable feet made in stainless steel. IPX5 protection rating. Electric power supply VAC 400 3N 50÷60 Hz - 16.4 kW.

## **Technical draw**







E: Electric power

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.