modular



Client _____ Quantity _____

Project _____ Position _____

REFRIGERATION

Model: TS16/1MR-490-07 **Cod:** HT10380000214

Technical data

Modularity:	Without top
Dimensions (mm):	1600x680x590
Total eletric power (kW):	0,81
Electric power (V):	220-240
Ampere (A):	3,7
Frequency (Hz):	50-60
Net volume (m3):	0,642
Packing dimensions (mm):	1875x800x998
Gross weight (kg):	95
Gross volume (m3):	1,500

Features

Grill:	GN1/1 coated grids
Working top:	Special for overlapping kitchen top modules Roc
Handles:	AISI 304 stainless steel, 2 mm thick
Drawer guides:	Full extension


In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previosly or subsequently sold.

modular

Refrigerated base 3 doors -2°+8°C remote

3-door refrigerated base unit, remote engine. Made entirely of AISI 304 18/10 stainless steel with 60 mm thick insulation obtained with CFC and HCFC-free polyurethane resins. Reversible self-closing doors with 105° stop, equipped with triple chamber geometry gasket with D7 compound. Ventilated refrigeration controlled by digital thermostat. Automatic electric defrosting system and elimination of condensation water by means of the heat dissipated by the refrigerant system. Operation in Climatic Class 5. Set up for R452A gas operation. Temperature -2°/+8° C. Power: 0.85 kW. Voltage: 220-240V/1N/50/60 Hz. Fixing kit to cookign element included. Engine not included

Technical draw



G: Gas connection 1/2"

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previosly or subsequently sold.