



Client _____ Quantity _____

Project _____ Position _____

ROC 700

Model: R70/120TPPFGF/P

Cod: MP01054113013

Technical data


| | |
|------------------------------|----------------------|
| Modularity: | On cabinet with door |
| Dimension (mm): | 1200x730x870 |
| Oven dimension (mm): | 555x660x289 |
| Total gas power (Kcal/h): | 30525 |
| Total gas power (kW): | 35,5 |
| Whole-plate power gas (kW): | 6 |
| Oven type: | Static oven |
| Oven power (kW): | 8 |
| Oven temperature range (°C): | 95-300 |
| Gas connection: | 1/2" |
| Net volume (m3): | 0,762 |
| Packing dimensions (mm): | 1280x856x1109 |
| Gross weight (kg): | 186,1 |
| Burner power 1 (kW): | 3,5 |
| Burner power 2 (kW): | 6 |
| Burner power 3 (kW): | 6 |
| Burner power 4 (kW): | 6 |
| Gross volume (m3): | 1,215 |

Features

| | |
|--------------|--|
| Working top: | Made of AISI 304 stainless steel with a thickness of 20/10 mm |
| Knobs: | Made of aluminum with IPX5 water protection |
| Handles: | The brushed aluminum handles allow for a secure and sturdy grip with a ergonomic lines |
| Flue: | Removable gas exhaust flue grill made of cast iron |
| Kit Gas: | Natural gas conversion kit 30/50 m/bar (tested with natural gas G20) |

Gas solid top range with 4 burners on gas static oven and neutral counter with door. Side panels, bottom and back made in stainless steel. Top made in AISI 304 thickness 20/10 designed for flush alignment. Rear flue made in enamelled cast-iron. Cooking plate made in extra-thick cast iron with extractable central plate. The central zone can reach 500°C while decreasing awards (to 300 °C). Heating by cast iron burner with 6 kW power. Gas supply by means of safety tap with pilot flame and safety thermocouple. Ignition by means of piezoelectric device with waterproof cap. Plate dimensions 760x540. Rapid burners made in cast iron and brass sealed to the top. Gas supply by safety taps with thermocouple and pilot burner for the automatic ignition of main burner. Radiused corners top, easy to clean, equipped with high thick enamelled cast-iron hobs resistant to acid, alkali and flame. Nr.3 burner 6 kW and n°1 burner 3,5 kW (Available burner powers 3,5 kW, 6 kW). Gas oven GN 2/1 equipped with thermostatic valve for temperature regulation from 50° C to 300 °C. Oven stabilized burner with piezoelectric ignition equipped with pilot flame and safety thermocouple. Cooking chamber made in stainless steel. Oven inner door made in stainless steel with labyrinth seal. Oven power 8 kW. Special design knobs to avoid water penetration in the control panel. Adjustable feet made in stainless steel. IPX5 protection rating. Gas total power 35,5 kW.

Technical draw



G: Gas connection 1/2"