

| Client | Quantity |
|---------|----------|
| Project | Position |

ROC 900

Model: R90/80TPE/P Cod: MP01054124003

Technical data

| Modularity: | On cabinet with doors |
|---------------------------|-----------------------|
| Dimensions (mm): | 800x900x870 |
| Total eletric power (kW): | 13,6 |
| Electric power (V): | 380-415 |
| Ampere (A): | 31 |
| Phases: | 3N |
| Cable section (mmq): | 5G6 |
| Frequency (Hz): | 50-60 |
| Drain size: | 1" |
| Net volume (m3): | 0,626 |
| Packing dimensions (mm): | 880x1026x1109 |
| Gross weight (kg): | 149 |
| Gross volume (m3): | 1,001 |

Features

| Working top: | Made of AISI 304 stainless steel with a thickness of 20/10 mm |
|--------------|--|
| Knobs: | Made of aluminum with IPX5 water protection |
| Handles: | The brushed aluminum handles allow for a secure and sturdy grip with a ergonomic lines |
| Flue: | Removable made of cast iron |


In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.





Electric solid top, on cabinet with doors

Electric solid top with 4 zones, model on cabinet with doors. Side panels, bottom and back made in stainless steel. Top made in AISI 304 thickness 20/10 with control edge for liquid collection Rear flue made in enamelled cast-iron; designed for flush alignment. Cooking plate made with high thick steel 16M06. 4 indipendent cooking zones each with 3.4 kW power, marked with a satin cooking surface. Safety thermosat with automatic recovery. Lamp to indicate heating activation and proper working of the equipment. Special design knobs to avoid water penetration in the control panel. Base completely made in stainless steel. Presses hinged doors. Ergonomic handle. Adjustable feet made in stainless steel. IPX5 protection rating. Electric power supply VAC 400 3N 50÷60 Hz - 13,6 kW.

Technical draw







E: Electric power

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.