

Client _____ Quantity _____
Project _____ Position _____

ROC 700

Model: R70/40PVE/T

Cod: MP01094123001



Technical data


Modularity:	Top
Dimension (mm):	400x730x280
Total electric power (kW):	5
Electric power (V):	380-415
Ampere (A):	11,5
Phases:	3N
Cable section (mmq):	5G2,5
Frequency (Hz):	50/60
Net volume (m3):	0,082
Packing dimensions (mm):	480x856x475
Gross weight (kg):	25,4
Gross volume (m3):	0,195

Features

Working top:	Made of AISI 304 stainless steel with a thickness of 20/10 mm
Knobs:	Made of aluminum with IPX5 water protection
Flue:	Removable gas exhaust flue grill made of cast iron

Glass ceramic hob with 2 cooking zones,, counter top model. Side panels, bottom and back made in stainless steel. Glass ceramic hob sealed to the top with 2 indipendent cooking zone each equipped with a 2.5 kW radiating element diam.230 mm. and relevant energy regulator. Top designed for flush alignment. Cooking zone marked with a screen printed outline on the glass. Lamps on control panel to indicate heating activation and the proper equipment operation. Special design knobs to avoid water penetration in the control panel. IPX5 protection rating. Adjustable feet. Electric power supply VAC 400 3N 50÷60 Hz - 5 kW.

Technical draw



E: Electric power