

Client	Quantity
Project	Position

ROC 700

Model: R70/80BMG/A Cod: MP01254113004

Technical data

Modularity:	On open cabinet
Dimensions (mm):	800x730x870
Total gas power (Kcal/h):	5160
Total gas power (kW):	6
Nr. Wells:	1
Well litres 1:	39
Well dimensions 1 (mm):	730x516x155
Gas connection:	1/2"
Drain size:	1"
Net volume (m3):	0,508
Packing dimensions (mm):	880x856x1109
Gross weight (kg):	71
Gross volume (m3):	0,835

Features


Working top:	Made of AISI 304 stainless steel with a thickness of 20/10 mm
Knobs:	Made of aluminum with IPX5 water protection
Flue:	Removable gas exhaust flue grill made of cast iron
Water inflow:	Manual input
Kit Gas:	Natural gas conversion kit 30/50 m/bar (tested with natural gas G20)


In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.




Gas bain-marie GN 1/1, model on open counter. Side panels, bottom and back made in stainless steel. Top made in AISI 304 thickness 20/10 designed for flush alignment. Rear flue made in enamelled cast-iron. Well made in stainless steel AISI 304. Heating by means of steel burner with stabilized flame complete with pilot flame and safety thermocouple. Gas supply by means of safety tap with temperature regulation from 30 °C to 90 °C. Ignition by piezoelectric device. Water drain by means of overflow system and vertical drain. Special design knobs to avoid water penetration in the control panel.Base completely made in stainless steel. Adjustable feet made in stainless steel. IPX5 protection rating. Gas total power 6 kW.

Technical draw







G: Gas connection 1/2"

D: Drain for water

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.