



Client	Quantity
Project	Position

## **ROC 900**

Model: R90/80FRGV/2V22/P Cod: MP01294114004

## **Technical data**

Modularity:	On cabinet with doors
Dimensions (mm):	800x900x870
Total gas power (Kcal/h):	34394
Total gas power (kW):	40
Nr. Wells:	2
Well litres 1:	22
Well litres 2:	22
Well dimensions 1 (mm):	309x442x318
Well dimensions 2 (mm):	309x442x318
Gas connection:	1/2"
Net volume (m3):	0,626
Packing dimensions (mm):	880x1026x1274
Gross weight (kg):	119,1
Gross volume (m3):	1,150

## **Features**


	_
Working top:	Made of AISI 304 stainless steel with a thickness of 20/10 mm
Type of heating:	Direct
Knobs:	Made of aluminum with IPX5 water protection
Flue:	Removable made of cast iron
Heating:	Heating pipes in the well
Kit Gas:	Natural gas conversion kit 30/50 m/bar (tested with natural gas G20)


In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.




Gas fryer with 1 wells 22+22 liters, model on cabinet with doors. Side panels, bottom and back made in stainless steel. Top made in AISI 304 thickness 20/10 designed for flush alignment. Rear flue made in enamelled cast-iron. Deep pressed wells with front expansion zone for oil collection and cold zone for food particles collection. Heating by means of high efficiency stainless steel burners located inside the well. Ignition by means of piezoelectric device. Safety thermostat with manual reset. Equipped with 1 basket 1/1 and 2 baskets 1/2 made of chrome plated steel and thermoplastic handle. Adjustable feet made in stainless steel. IPX5 protection rating. Gas total power 40 kW.

## **Technical draw**







G: Gas connection 1/2"

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.