

| Client | Quantity |
|---------|----------|
| Project | Position |

FUN 700

Model: F70/70FTE/LR/P

Market: Extra UE

Cod: MP01372123026

Technical data

| Modularity: | On cabinet with doors |
|-------------------------------------|-----------------------|
| Dimension (mm): | 700x700x850 |
| Total eletric power (kW): | 9 |
| Cooking zone dimensions 1 (LxD mm): | 696x520 |
| Electric power (V): | 380-415 |
| Ampere (A): | 14 |
| Phases: | 3N |
| Cable section (mmq): | 5G2,5 |
| Frequency (Hz): | 50-60 |
| Net volume (m3): | 0,417 |
| Packing dimensions (mm): | 776x776x1180 |
| Gross weight (kg): | 94 |
| Gross volume (m3): | 0,711 |

Features

| Working top: | Made of AISI 304 stainless steel with a thickness of 10/10 mm |
|--------------------|---|
| Material of plate: | Mild steel |
| Knobs: | Knobs are made from a sturdy heat-resistant polymer blend and are equipped with liquid antileakage washer |
| Handles: | Brushed aluminum finish |
| Plate: | In mild steel |
| | |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.





Electric griddle, 2/3 smooth 1/3 ribbed mild steel plate, on cabinet


with doors

Electric griddle plate 2/3 Smooth 1/3 grooved on cabinet with doors. Top made of AISI 304 stainless steel thickness 8/10; covering in AISI 304 stainless steel thickness 8/10; external reinforcements made of anti-corrosion material (aluminised sheet metal); bottoms and internal parts in AISI 430 steel; flue cover in enamelled steel. Equipped with two independent cooking zones. Provided with front groove, extractable drawer for grease collection and splash guard on three sides. Cooking zone equipped with 3 heating elements which are thermostat controlled in a range of use from 50° to 300° C. Safety thermostat and indicator lights to show correct operation. 6 plates x 1.5 kW. Total power 9 kW. Cooking plate dimensions 695x550 mm. Electrical power supply VAC 400 + 3N 50÷60 Hz.

Technical draw







E: Electric power

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.