

| Client | Quantity |
|---------|----------|
| Project | Position |

ROC 900

Model: R90/40FTG/R/T

Market: Extra UE

Cod: MP01374114007



Technical data

| Modularity: | Тор |
|-------------------------------------|--------------|
| Dimensions (mm): | 400x900x280 |
| Total gas power (Kcal/h): | 6019 |
| Total gas power (kW): | 7 |
| Cooking zone dimensions 1 (LxD mm): | 335x700 |
| Gas connection: | 1/2" |
| Net volume (m3): | 0,101 |
| Packing dimensions (mm): | 480x1026x475 |
| Gross weight (kg): | 49 |
| Gross volume (m3): | 0,234 |

Features

| Working top: | Made of AISI 304 stainless steel with a thickness of 20/10 mm |
|------------------------------|--|
| Material of plate: | Mild steel |
| Plate finish: | Ribbed |
| Knobs: | Made of aluminum with IPX5 water protection |
| Flue: | Removable made of cast iron |
| Liquid collection container: | Removable and dishwasher safe |
| Plate: | In mild steel |
| Upright Splash guard: | On two sides (optional) |
| Kit Gas: | Natural gas conversion kit 30/50 m/bar (tested with natural gas G20) |
| | |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.




Gas griddle, ribbed mild steel plate, top

Gas griddle with grooved plate, counter top model. Side panels, bottom and back made in stainless steel. Top made in AISI 304 thickness 20/10. Rear flue made in enamelled cast-iron. Designed for flush alignment. Recessed (4 cm) hotplate fully welded and sealed to the top. Satin cooking surface with cold zone at the front. Round hole and extractable drawer for grease drain and collection. Plate dim.335x700 mm. Heating by means of steel burner with stabilized flame complete with pilot flame and safety thermocouple. Cooking temperature manually controlled by gas supply safety tap. Automatic ignition by means of piezoelectric device with waterproof cap. Special design knobs to avoid water penetration in the control panel. Adjustable feet. IPX5 protection rating. Gas total power 7 Kw.

Technical draw







G: Gas connection 1/2"

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.