

Client \_\_\_\_\_ Quantity \_\_\_\_\_  
 Project \_\_\_\_\_ Position \_\_\_\_\_

## ROC 900

Model: R90/80GRLG/T  
 Market: Extra UE

Cod: MP01454114004



### Technical data




|                                     |                          |
|-------------------------------------|--------------------------|
| Modularity:                         | Top                      |
| Dimensions (mm):                    | 800x900x280              |
| Total gas power (Kcal/h):           | 16338                    |
| Total gas power (kW):               | 19                       |
| Cooking zone dimensions 1 (LxD mm): | n°2 981.109.13 (184x690) |
| Cooking zone dimensions 2 (LxD mm): | n°2 981.109.13 (184x690) |
| Gas connection:                     | 1/2"                     |
| Net volume (m3):                    | 0,202                    |
| Packing dimensions (mm):            | 880x1026x1109            |
| Gross weight (kg):                  | 94,9                     |
| Gross volume (m3):                  | 1,001                    |

### Features

|                              |  |
|------------------------------|--|
| Grill:                       | In cast iron   |
| Working top:                 | Made of AISI 304 stainless steel with a thickness of 20/10 mm        |
| Knobs:                       | Made of aluminum with IPX5 water protection                          |
| Liquid collection container: | Removable and dishwasher safe  |
| Upright Splash guard:        | On three sides   |
| Kit Gas:                     | Natural gas conversion kit 30/50 m/bar (tested with natural gas G20) |

Gas lava stone grill,, counter top model. Side panels, bottom and back made in stainless steel. Top made in AISI 304 thickness 20/10. designed for flush alignment. Lava stone support made in Stainless steel mesh AISI 304. V shaped hob grill made in stainless steel. Lever-controlled grill raising mechanism to control distance of grill from brazier with one hand. Grease collection by an upper front extractable tray and by an extractable drawer located under the heating zone. Two independent cooking zones. Heating by means of steel burner with stabilized flame complete with pilot flame and safety thermocouple. Cooking temperature manually controlled by gas supply safety tap. Automatic ignition by means of piezoelectric device with waterproof cap. Special design knobs to avoid water penetration in the control panel. Apparecchiatura dotata di Adjustable feet. IPX5 protection rating. Gas total power 19 kW.

**Technical draw**



G: Gas connection 1/2"