



Client	Quantity	
Proiect	Position	
riulect	FUSILIUII	

## **ROC 900**

Model: R90/80PGD/100 Cod: MP01534114002

## **Technical data**

<b>A</b> 1.1. %	
Modularity:	On closed cabinet
Dimensions (mm):	800x900x870
Total eletric power (kW):	0,1
Total gas power (Kcal/h):	18057
Total gas power (kW):	21
Nr. Wells:	1
Well litres 1:	100
Well dimensions 1 (mm):	Ø596x405
Gas connection:	1/2"
Electric power (V):	220-240
Ampere (A):	0,5
Phases:	1
Cable section (mmq):	3G1
Frequency (Hz):	50
Hot water inflow:	3/4"
Hot water temperature (°C):	40
Hot water pressure (bar):	Max pressure 5 bar
Cold water inflow:	3/4"
Cold water pressure (bar):	Max pressure 5 bar
Drain size:	2"
Net volume (m3):	0,626
Packing dimensions (mm):	880x1272x1274
Gross weight (kg):	131
Gross volume (m3):	1,426

## **Features**


Working top:	Made of AISI 304 stainless steel with a thickness of 20/10 mm
Type of heating:	Direct
Knobs:	Made of aluminum with IPX5 water protection
Water inflow:	With solenoid valve
Kit Gas:	Natural gas conversion kit 30/50 m/bar (tested with natural gas G20)


In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.


liters

Gas boiling pan with direct heating capacity 100 liters. Side panels, bottom and back made in stainless steel. Pressed top made in AISI 304 thickness 20/10 equipped with control edge. Designed for flush alignment. Rear flue made in enamelled cast-iron. Cooking weel walls in stainless steel AISI 304 and bottom in AISI 316. Balanced lid in stainless steel AISI 304 equipped with athermic handle. Structure made in stainless steel. Thermal insulation obtained by means of high thickness panels. Water charge (hot and cold) by means of electrovalve. Well drain hole with extractable filter. 2" front drain tap made in chromed brass with insulated handle. Heating by means of high efficiency tubular burners in stainless steel. Cooking temperature controlled by safety tap equipped with termocouple and pilot burner. Ignition by piezoelectric device. Special design knob to avoid water penetration in the control panel. Adjustable feet made in stainless steel. IPX5 protection rating. Gas total power 21 kW. Electric supply VAC 230 1N 50 Hz- 0.3 kW

## **Technical draw**







Water inflow 3/4"

G: Gas connection 1/2" E: Electric power H2O:

A1: Hot water inflow A2: Cold water inflow D: Drain for water

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.