



Client	Quantity
Project	Position

ROC 700

Model: R70/80BRG/60F/M

Market: Extra UE

Cod: MP01614113002

Technical data

Dimensions (mm): 800x730x870 Total eletric power (kW): 0,2 Total gas power (KCal/h): 12038 Total gas power (kW): 14 Cooking zone dimensions 1 (LxD mm): fondo vasca 680x397 Mr. Wells: 1 Vell litres 1: 60 Well dimensions 1 (mm): 680x397x170 Gas connection: 1/2" Electric power (V): 220-240 Ampere (A): 1,5 Phases: 1 Cable section (mmq): 3G1 Frequency (Hz): 50 Cold water inflow: 3/4" Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145 Gross volume (m3): 0,835	Modularity:	On closed cabinet
Total gas power (Kcal/h): 12038 Total gas power (kW): 14 Cooking zone dimensions 1 (LxD mm): fondo vasca 680x397 Nr. Wells: 1 Well litres 1: 60 Well dimensions 1 (mm): 680x397x170 Gas connection: 1/2" Electric power (V): 220-240 Ampere (A): 1,5 Phases: 1 Cable section (mmq): 3G1 Frequency (Hz): 50 Cold water inflow: 3/4" Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Dimensions (mm):	800x730x870
Total gas power (kW): 14 Cooking zone dimensions 1 (LxD mm): fondo vasca 680x397 mm): Nr. Wells: 1 Well litres 1: 60 Well dimensions 1 (mm): 680x397x170 Gas connection: 1/2" Electric power (V): 220-240 Ampere (A): 1,5 Phases: 1 Cable section (mmq): 3G1 Frequency (Hz): 50 Cold water inflow: 3/4" Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Total eletric power (kW):	0,2
Cooking zone dimensions 1 (LxD mm): fondo vasca 680x397 mm): Nr. Wells: 1 Well litres 1: 60 Well dimensions 1 (mm): 680x397x170 Gas connection: 1/2" Electric power (V): 220-240 Ampere (A): 1,5 Phases: 1 Cable section (mmq): 3G1 Frequency (Hz): 50 Cold water inflow: 3/4" Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Total gas power (Kcal/h):	12038
mm): 1 Nr. Wells: 1 Well litres 1: 60 Well dimensions 1 (mm): 680x397x170 Gas connection: 1/2" Electric power (V): 220-240 Ampere (A): 1,5 Phases: 1 Cable section (mmq): 3G1 Frequency (Hz): 50 Cold water inflow: 3/4" Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Total gas power (kW):	14
Well litres 1: 60 Well dimensions 1 (mm): 680x397x170 Gas connection: 1/2" Electric power (V): 220-240 Ampere (A): 1,5 Phases: 1 Cable section (mmq): 3G1 Frequency (Hz): 50 Cold water inflow: 3/4" Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145		fondo vasca 680x397
Well dimensions 1 (mm): 680x397x170 Gas connection: 1/2" Electric power (V): 220-240 Ampere (A): 1,5 Phases: 1 Cable section (mmq): 3G1 Frequency (Hz): 50 Cold water inflow: 3/4" Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Nr. Wells:	1
Gas connection: 1/2" Electric power (V): 220-240 Ampere (A): 1,5 Phases: 1 Cable section (mmq): 3G1 Frequency (Hz): 50 Cold water inflow: 3/4" Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Well litres 1:	60
Electric power (V): 220-240 Ampere (A): 1,5 Phases: 1 Cable section (mmq): 3G1 Frequency (Hz): 50 Cold water inflow: 3/4" Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Well dimensions 1 (mm):	680x397x170
Ampere (A): Phases: Cable section (mmq): Frequency (Hz): Cold water inflow: Cold water pressure (bar): Net volume (m3): Packing dimensions (mm): Gross weight (kg): 1,5 1,5 1 Ampere (A): Again Again	Gas connection:	1/2"
Phases: 1 Cable section (mmq): 3G1 Frequency (Hz): 50 Cold water inflow: 3/4" Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Electric power (V):	220-240
Cable section (mmq): 3G1 Frequency (Hz): 50 Cold water inflow: 3/4" Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Ampere (A):	1,5
Frequency (Hz): 50 Cold water inflow: 3/4" Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Phases:	1
Cold water inflow: 3/4" Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Cable section (mmq):	3G1
Cold water pressure (bar): Max pressure 5 bar Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Frequency (Hz):	50
Net volume (m3): 0,508 Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Cold water inflow:	3/4"
Packing dimensions (mm): 880x856x1109 Gross weight (kg): 145	Cold water pressure (bar):	Max pressure 5 bar
Gross weight (kg): 145	Net volume (m3):	0,508
	Packing dimensions (mm):	880x856x1109
Gross volume (m3): 0,835	Gross weight (kg):	145
	Gross volume (m3):	0,835

Features

Working top:	Made of AISI 304 stainless steel with a thickness of 20/10 mm
Material of plate:	Iron
Plate finish:	Smooth
Tipologia ribaltamento:	Motorizzata
Knobs:	Made of aluminum with IPX5 water protection
Flue:	Removable gas exhaust flue grill made of cast iron
Water inflow:	With solenoid valve
Kit Gas:	Natural gas conversion kit 30/50 m/bar (tested with natural gas G20)


In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.





Motorized tilting gas bratt pan, iron well, capacity 60 litres

Gas motorized tilting brattpan capacity 60 lt. Side panels, bottom and back made in stainless steel. Top designed for flush alignment. Rear flue made in enamelled cast-iron. Cooking well made in stainless steel AISI 304, bottom made in mild steel. MotorizedI well tilting on front axle. Well water charge by means of filling tap located on the flue. Well lid made in stainless steel AISI 304 with ergonomic and athermic handle. Heating by means of high efficiency tubular burners in stainless steel. Cooking temperature controlled by safety tap equipped with termocouple and pilot burner. Ignition by means of piezoelectric device. Special design knobs to avoid water penetration in the control panel. Adjustable feet made in stainless steel. IPX5 protection rating. Gas total power 14 kW. Electric supply VAC 230 1N 50 Hz- 0.2 kW

Technical draw







G: Gas connection 1/2" E: Electric power H2O: Water inflow 3/4"

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.